



LC-POWER

LC8750III V2.3 - Prophecy 3

Metatron Series



ATX V2.3 / EPS 12V

Due to its current ATX V2.3 standard, the Prophecy 3 power supply works perfectly in modern as well as in older computer systems.

Free-Plug Modular Cable Management

Featuring the free-plug technology, Prophecy 3 offers a progressive modular cable management to improve the airflow inside the computer case.

Dual/Quad Core Support

The power supply supports all modern DualCore, QuadCore and server systems.

PCI-Express x 4

Includes four PCI-Express V2.0 6+2 pin connectors for high end gaming.

+12V Rail

Prophecy 3 features one +12V rail (62A) to provide stability and power for high-performance systems.

High Efficiency / 80 PLUS® BRONZE certified

Modern technology decreases the standby mode power consumption (<0,5W) and increases the efficiency of the power supply up to $\geq 85\%$.

Active PFC

Use active power factor correction (>0.99) to provide additional security to your system.

Advanced Security Circuitry

Over-Voltage Protection (OVP), Over-Current Protection (OCP), Over-Power Protection (OPP), Under-Voltage Protection (UVP), Short-Circuit Protection (SCP)

Automatic Voltage Detection

The power supply features an automatic voltage detection (110V~240V) so that it is usable in different infrastructural environments (e.g. Europe, USA)

135mm Fan

Enjoy ultra silent work thanks to the high quality 135 mm fan with blue LEDs.

Connectors:

1x 20+4 pin mainboard	55 cm
1x 4+4 pin mainboard 12V (8 pin EPS)	60 cm
4x PCI-Express V2.0 6+2 pin	2x 55/2x 70 cm
6x SATA	2x 50/2x 65/2x 80 cm
6x PATA	2x 45/2x 60/2x 75 cm
2x FDD	90 cm

Barcode:	4260070125003
Manufacturer code:	LC8750III V2.3
Mark of conformity:	TÜV, CE
Fan:	135 mm
PFC:	active
Weight (retail):	2,524 kg
Dimension:	86 x 150 x 158 mm (height x width x depth)

Power rating:	
+3,3V:	20A
+5V:	20A
max. combined:	100W
+12V:	62A
max. combined:	744W
max. combined:	750W
Standby:	<0,5W