
Metatron Series



_C-POWEF

LC8750RGB V2.3 - Prophecy RGB







ATX V2.3 / EPS 12V

Due to its current ATX V2.3 standard, the Prophecy RGB power supply works perfectly in modern as well as in older computer systems.

Free-Plug Modular Cable Management

Featuring the free-plug technology, Prophecy RGB offers a progressive modular cable management to improve the airflow inside the computer case.

Dual/Quad Core Support

The power supply supports all modern DualCore, QuadCore and server systems.

Includes four PCI-Express V2.0 6+2 pin connectors for high end gaming.

Prophecy RGB features one +12V rail (62,5A) to provide stability and power for high-performance systems

High Efficiency / 80 PLUS® BRONZE certified

Modern technology decreases the standby mode power consumption (<0,5W) and increases the efficiency of the power supply up to ≥85%.

Use active power factor correction (>0.99) to provide additional security to your system.

Over-Voltage Protection (OVP), Over-Current Protection (OCP), Over-Power Protection (OPP), Under-Voltage Protection (UVP), Short-Circuit Protection (SCP)

Automatic Voltage Detection

The power supply features an automatic voltage detection (110V~240V) so that it is usable in different infrastructural environments (e.g. Europe, USA)

135mm RGB Fan

Enjoy ultra silent work thanks to the high quality 135 mm RGB fan.

Colours can be controlled via the mainboard's RGB software (digital RGB / ARGB) or via the switch on the back of the power supply

Connectors:

1x 20+4 pin mainboard 1x 4+4 pin mainboard 12V (8 pin EPS)

6x SATA

4x PCI-Express V2.0 6+2 pin 6x PATA 2x FDD

55 cm 60 cm 2x 55/2x 70 cm 2x 50/2x 65/2x 80 cm 2x 45/2x 60/2x 75 cm Barcode: Manufacturer code: Mark of conformity: PFC:

Weight (retail): Dimension:

4260070126673 LC8750RGB V2.3 TÜV. CE 135 mm active 2,5 kg

86 x 150 x 158 mm (height x width x depth) Power rating: +3,3V:

20A +5V: 20A max. combined: 130W

+12V: 62.5A max. combined: 750W

750W max. combined: <0,5W

Standby: